


Hospital grade plugs & connectors

Hospital grade plugs & connectors

Product description

2-pole, 3-wire grounding
15A, 125V/AC; 20A, 125V/AC
15A, 250V/AC; 20A, 250V/AC
NEMA 5-15, 5-20, 6-15, 6-20



Design features

- Rated and marked "Hospital Grade" and identified with a green dot symbol for easy identification
- Back-wired dead-front construction for a secure wiring solution
- EPDM gasket seals cord hole on ultra grip plugs and connectors to ensure strong sealing of wiring chamber
- Dual dovetail design on ultra grip series provides for superior cord grip alignment and retention
- Removable inserts on ultra grip series and dual range cord grip clamps on safety grip series
- Combination head screws: U.S. Phillips/Slotted; Canadian Robertson/Slotted
- Quick grip single-piece hinged body reduces number of assembly screws to speed installation
- Auto grip plugs and connectors feature automatic cord grip assembly clamps the flexible cord to reduce wiring time, saving time and money



AH8215HG



AH8215HGC



AH8215HGAC



AH8115W



5266NHG



5269NHG

Hospital grade plugs & connectors



Rating		A	V/AC	NEMA	Description	Cord diameter	Color suffix	Catalog no.	
15	125	5-15			Ultra grip plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8215HG	•
					Safety grip plug	0.30"-0.66" (7.6-16.7mm)	C	□ AH8215HGC	•
					Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8215HGA	•
					Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	C	□ AH8215HGAC	•
					Quick grip plug	0.22"-0.67" (5.6-16.9mm)	W	□ AH8115W	
					Auto grip straight body plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ 5266NHG	
					Auto grip isolated ground plug	0.30"-0.66" (7.6-16.7mm)	RN	□ IG5266NHG	
					Ultra grip connector	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8219HG	•
					Safety grip connector	0.30"-0.66" (7.6-16.7mm)	C	□ AH8219HGC	•
					Quick grip connector	0.22"-0.67" (5.6-16.9mm)	W	□ AH8119W	•
					Auto grip straight body connector	0.30"-0.66" (7.6-16.7mm)	BK & W	□ 5269NHG	•
15	250	6-15			Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8225HGA	
					Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	C	□ AH8225HGAC	
20	125	5-20			Ultra grip plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8315HG	•
					Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8315HGA	•
					Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	C	□ AH8315HGAC	•
					Auto grip straight body plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ 5366NHG	•
					Ultra grip connector	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8319HG	•
					Auto grip straight body connector	0.30"-0.66" (7.6-16.7mm)	BK & W	□ 5369NHG	•
20	250	6-20			Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	BK & W	□ AH8325HGA	•
					Safety grip angled plug	0.30"-0.66" (7.6-16.7mm)	C	□ AH8325HGAC	•

Color ordering information

BK (Black), RN (Orange), C (Clear), W (White)

BK	RN	C	W
(Black)	(Orange)	(Clear)	(White)

Testing & code compliance: Listed to UL 498, file no. E3663, E146159 (Quick grip series), UL verified to Federal Spec. WC-596F, CSA certified to C22.2, no. 42. (Quick grip series). **Material characteristics:** Nylon, Environmental: Flammability meets UL 94 requirements; Quick grip V2 rated, auto grip V2 rated, Temperature rating: quick grip -40°C to 75°C (-40°F to 167°F).

Indicates USMCA compliant

Compliances, specifications and availability are subject to change without notice.